



T:1.6 Dimensions of PC board holes
Tolerance : ±0.05(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DC20-R37CSB	φ2.0	
DC25-R37CSB	φ2.5	
DC30-R37CSB	φ3.0	

6	HOUSING	1	PBT	UL-94V0(BLACK)
5	COVER	1	PBT	UL-94V0(BLACK)
4	PIN	1	H59(COPPER ALLOY)	Ni PLATED
3	SHUNT TERMINAL	1	C2680 t=0.45	Ag PLATED
2	TIP SPRING	1	C5191 t=0.30	Ag PLATED
1	CENTER PIN TERMINAL	1	C2680 t=0.45	Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED. TOLERANCE ON DECIMAL:±0.3

DIMENSIONS ARE IN MILLIMETERS		SPARKTRONIC CO., LTD.		RoHS COMPLIANT	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PART NO.	DC30,25,20-R37CSB	TITLE: DIA. 3.00MM, 2.50MM, 2.00MM DC POWER JACK RIGHT ANGLE DIP TYPE	
LINEAR	0.0±0.25 0.00±0.15	DATE	July / 12 / 2023		
ANGLES	± 3	NOT SCALED DRAWING		DRAWING NO.	DC30,25,20-R37CSB