



Specification

Test Voltage.....Ac 2000V for 1 Minute
 Insulation Resistance.....1000M ohm min at DC 500V
 Contace Resistance.....15Mohm mcx.

NOTE: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS-C3604
2. CONNECTOR INTERFACE PER MIL-STD-348A
3. PART TO BE CLEAN AND FREE BURRS
4. NICKEL PL 70 μ" THICK OVER COPPER STRIKE
5. GOLD PL 1-3 μ" OVER NICKEL PL 70 μ" THICK OVER COPPER STRIKE

3	Insulator	Teflon	White
2	Contact	Brass	Nickel
1	Body	Brass	Nickel
No	Description	Material	Finish

DIMENSIONS ARE IN MILLIMETERS		SPARKTRONIC CO., LTD.		RoHS COMPLIANT		
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6= ±0.2 6-30= ±0.4 30-120= ±0.6 120-315= ±1.0 315-1000= ±1.6 1000-2000= ±2.4		PART NO.	P971CU-XNNT50		TITLE: EUROPEAN(PAL) R/A PCB MOUNT JACK	
		DATE	September / 14 / 2010			
		NOT SCALED DRAWING			DRAWING NO.	P971CU-XNNT50